

Industrial Panel PC

Model SK-23.6GB-WD03



Features

- Industrial 23.6" IPS LCD with 50K Lifetime LED Backlight
- Intel® i3-7th/i5-7th/i7-7th optional, with 4/8/16GB RAM 128/256/512GB SSD
- 10 Point Capacitive G+G Touch Screen
- Supports wide operating temperatures -10~50°C
- IP65 certified front panel protection

senke®

Introduction

The SK-23.6GB-WD03 industrial touch panel pc with a 23.6" IPS LCD screen, low power embedded •Intel® i3-7th/i5-7th/i7-7th optional, with 4/8/16GB RAM 128/256/512GB SSD, provides computing performance in a compact system. To enhance its durability, the SK-23.6GB-WD03 is designed with IP65 front protection, aluminium front bezel and 10 point Capacitive G+G touch screen. It supports wide operating temperatures -10~50°C and includes full size mini-PCIe slot to extend the functionality and meet a variety of automation applications needs.

Specifications

General

Certification	CCC, CE, FCC, ISO9001
Cooling system	Fanless
Dimensions	578.9*353.9*65.9 mm
Enclosure front bezel	Front bezel : Aluminum Back housing : Cold rolled steel plate
Mounting	Default wall mounting bracket
OS support	Microsoft® Windows 10, 64bit Default windows 10 English professional trial Version
Optional color	Black
Weight (Net)	3.5 kg
Weight (Gross)	6 kg
Package size	45*33*14cm

System Hardware

CPU	Intel® i3-7th/i5-7th/i7-7th
RAM	4/8/16GB DDR4
ROM	128/256/512GB SSD

I/O

12V input*1
HDMI x1
RS485*1, RS232*5
USB3.0*2, USB2.0*2
RJ45*2
Audio*1
Power*1

LCD Display

Display type	IPS LCD screen
Display size	521.2*293.2 mm (H*V)
Resolution	1920 x 1080
Max. colors	16.7 M
Luminance cd/m²	250
Viewing angle (H/V°)	178°/178°
Backlight life	50000 hrs
Contrast ratio	1500:1
Aspect ratio	16:9
Lifespan	36 million touches at single point
Touch type	10 Point Capacitive G+G touch screen
Response	≤5 ms

Environment

Humidity	10~ 95% RH @ 40°C, non-condensing
Protection	Front panel: IP65
Operating Temperature	-10 ~ 50°C
Storage Temperature	-30 ~ 70°C

Drawing

