

BORNE INTERACTIVE

Model SK-15G Intel i3



Features

- 15" IPS LCD with 50K Lifetime LED Backlight
- Processor Intel® i3 with 4GB DDR3 SDRAM 128GB SSD.
- Supports wide operating temperatures -10~50°C
- IP65 certified front panel protection
- 10 Point Capacitive G+G Touch Screen

Introduction

The SK-15G Kios all in one pc with a 15" IPS LCD screen, low power embedded Intel® Processor Intel® i3 with 4GB DDR3 SDRAM 128 GB SSD,provides computing performance in a compact system. To enhance its durability, the SK-15G is designed with IP65 front protection, aluminium front bezel and 10 point Capacitive G+G touch screen.It supports wide operating temperatures -10~50°C and includes full size mini-PCIe slot to extend the functionality and meet a variety of automation applications needs.

Specifications

General

|                       |                                                       |
|-----------------------|-------------------------------------------------------|
| Certification         | CCC,CE, FCC ,ISO9001,BIS,CCC                          |
| Cooling system        | Fan                                                   |
| Dimensions            | 297 x 378 x 58.5 mm                                   |
| Enclosure front bezel | Front bezel : Aluminum                                |
| Mounting              | Back housing : Cold rolled steel plate                |
| OS support            | Default wall mounting bracket                         |
| Optional color        | Microsoft @ Windows10,64bit                           |
| Weight (Net)          | Default windows 10 English professional trial Version |
| Weight (Gross)        | Silver or black                                       |
| Package size          | 6 kg                                                  |
|                       | 7.5 kg                                                |
|                       | 63.5 x 43.5 x 14.5 cm                                 |

System Hardware

|                 |                                    |
|-----------------|------------------------------------|
| CPU             | Intel® Core® i3 Processor 4GB DDR3 |
| Memory          | 128 GB SSD                         |
| Storage         | Full-size Mini PCI-E               |
| Expansion Slots | 100 Base-T x1                      |
| LAN             |                                    |

I/O

|                                      |    |
|--------------------------------------|----|
| Power x1                             |    |
| HDMI x1                              |    |
| VGA x1                               |    |
| USB x4                               |    |
| LAN x1 (RJ-45 )                      |    |
| Audio input                          | x1 |
| Audio output                         | x1 |
| Other customized Interface available |    |

LCD Display

|                      |                                      |
|----------------------|--------------------------------------|
| Display type         | IPS LCD screen                       |
| Display size         | 228 x 304 mm (H×V)                   |
| Resolution           | 1024 x 768                           |
| Max. colors          | 16.7 M                               |
| Luminance cd/m²      | 250                                  |
| Viewing angle (H/V°) | 178°/178°                            |
| Backlight life       | 50000 hrs                            |
| Contrast ratio       | 1500:1                               |
| Aspect ratio         | 16:9                                 |
| Lifespan             | 36 million touches at single point   |
| Touch type           | 10 Point Capacitive G+G touch screen |
| Response             | ≤5 ms                                |

Environment

|                       |                                   |
|-----------------------|-----------------------------------|
| Humidity              | 10~ 95% RH @ 40°C, non-condensing |
| Ingress Protection    | Front panel: IP65                 |
| Operating Temperature | -10 ~ 50°C                        |
| Storage Temperature   | -30 ~ 70°C                        |

Accessories

|                                     |
|-------------------------------------|
| Adaptor (DC 12-19V) (cable 1 meter) |
| Power plug ( cable 1.2 meter )      |
| K type bracket                      |

**SUPPORT MULTIPLE INFORMATION CHECKING SYSTEM**

Floor guide, System management, Information query, Traffic query, etc.

**10 POINT SENSITIVE TOUCH**

Sensitive multiple touch, Support multiple gesture, Easily to reach

**REMOTE OPERATION**