

## ZQ-DW970

### PRODUCT FEATURES

- PAD POS design, compact structure;
- 360 degrees vertical rotatable aluminum base;
- 120 degrees viewing angle adjustable design;
- Flat multi-point capacitive touch panel;
- CNC made and anodic oxidization painted base;
- Peripheral functions of MSR and Dallas Key modules optional available;
- Plenty of data ports available.



### SPECIFICATIONS

|                |                                                                               |                    |                           |
|----------------|-------------------------------------------------------------------------------|--------------------|---------------------------|
| CPU            | J6412 4 COEURS 2.6 GHz, 10nm CPU, 10W                                         | MSR                | Yes (optional)            |
| OS Supported   | Windows 64 bit                                                                | Dallas             | Yes (optional)            |
| Display Signal | LVDS                                                                          | Ports              | 2 x RS232 COM             |
| Screen         | 9.7" TFT LCD, 1024 x 768 (max.), 300CD/m <sup>2</sup>                         |                    | 1 x HDMI                  |
| Viewing Angle  | 150 degrees in vertical, 160 degrees in horizontal                            |                    | 4 x USB 3.0               |
| Touch Solution | 9.7" flat multi-point capacitive touch,<br>6H hardness, 86% transparency rate |                    | 2 x RJ45                  |
| RAM            | 4/8 GB DDR4 as standard                                                       |                    | 1 x DC Input, DC2.5       |
| Storage        | 64/128 / 256 SSD GB                                                           |                    | 2W                        |
| Network        | 100M adaptive                                                                 | Speaker (optional) | AC 100 ~ 240V / 47 ~ 63Hz |
| WIFI           | WIFI 802.11 b/g/n (2.4G)                                                      | Power Adaptor      | DC 12V 2.5A, DC2.5        |
|                |                                                                               | Work Environment   | -10~50 degree, 15%~90%    |

