










Product Feature

- Support WeChat, alipay and other payment bar code
- New decoding chip, interpretation of a variety of 1D/2D barcode
- Higher decoding accuracy
- Wire life more durable
- Plug and play, simple setup, fast use

Product Size







Specification

Performance Parameters

Light Sources: 617nm LED Aimer, White LED

1D: EAN13, EAN8, UPCA, UPCE0, UPCE1, Code 128, Code 39, Code 93, Supported Symbologies: Codabar, Interleave 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code 11,

MSI Code, MSI Plessey, RSS-14, Qualified RSS, Extended RSS.

2D: QR Code, Data Matrix(ECC200), PDF417.

Scan Type: Image CMOS 640*480 Image Sensor:

Manual/Continuous/Automatic Induction Scanning Scan Mode:

Precision: 1D ≥5mil, 2D ≥10mil

Yaw±60°, Rotation 360°, Pitch±60° Scan Angle: Depth of scan field: 35-190mm(EAN13, 13mil, PCS90%)

1/5million Error Rate:

USB-HID, RS232, USB-COM Interface:

Physical Parameters

Dimensions: 83mm*70mm*172mm

Weight: 112g Material: ABS+PC Cable Length: 2M

Environmental Parameters

Operating Temperature: -20°C~60°C Storage Temperature: -40°C~70°C

Relative Humidity: 5% ~95% RH(Non-condensing)

Shock Resistance: Withstands multiple times 1.5 meters drops to concrete

Electronic Parameters

Working Voltage: DC5V±5% Working Current: 120mA

Application









