


BORNE INTERACTIVE F-UM10,1"

Model SK-10.1GB

H : 99mm



Features

- Industrial 10.1" IPS LCD with 50K Lifetime LED Backlight
- Intel® J4415L, with 4GB RAM 64SSD
- 10 Point Capacitive G+G Touch Screen
- Supports wide operating temperatures -10~50°C
- IP65 certified front panel protection

senke®

Introduction

The SK-10.1GB industrial touch panel pc with a 10.1" IPS LCD screen, low power embedded ● Intel® J4415L, with 4GB RAM 64SSD, provides computing performance in a compact system. To enhance its durability, the SK-10.1GB is designed with IP65 front protection, aluminium front bezel and 10 point Capacitive G+G touch screen. It supports wide operating temperatures -10~50°C and includes full size mini-PCIe slot to extend the functionality and meet a variety of automation applications needs.

Specifications

General

Certification

CCC,CE, FCC ,ISO9001

System Hardware

CPU

Intel® J4415

RAM

4 GB RAM

ROM

64 GB SSD

I/O

12V input*1

HDMI x1

RS485*1,RS232*1

USB3.0*2,USB2.0*2

RJ45*2

Audio*1

Power*1

10 POINT SENSITIVE TOUCH

Touchscreen supports multi-touch gestures (Zhuji) in touch



LCD Display

Display type

IPS LCD screen

Display size

136 × 217 mm (H×V)

Resolution

1280 × 800

Max. colors

16.7 M

Luminance cd/m²

250

Viewing angle (H/V°)

178°/178°

Backlight life

50000 hrs

Contrast ratio

800:1

Aspect ratio

16:10

Lifespan

36 million touches at single point

Touch type

10 Point Capacitive G+G touch screen

Response

≤5 ms

Environment

Humidity

10~ 95% RH @ 40°C, non-condensing

Protection

Front panel: IP65

Operating Temperature

-10 ~ 50°C

Storage Temperature

-30 ~ 70°C

Senke®

