

Industrial Touch Panel PC

Model SK-17GB-W1



Features

- Industrial 17 inch IPS LCD with 50K Lifetime LED Backlight
- Intel® Core J6412 Processor with 8GB DDR4 RAM, 256G SSD
- Supports wide operating temperatures -10~50°C
- IP65 full protection
- 10 Point Capacitive G+G Touch Screen/ Single Point Resistance Touch Screen

Senke®

Introduction

Industrial touch panel PC with a 17 inch 15 inch IPS LCD screen, low power embedded Intel® CoreJ6412 Processor with 8GB DDR4 RAM, 256G SSD provides computing performance in a compact system. To enhance its durability, the IPC is designed with IP65 full protection, aluminum frame and 10 point Capacitive G+G touch screen. It supports wide operating temperatures -10~50°C and includes full size mini-PCIe slot to extend the functionality and meet a variety of automation applications needs.

Specifications

General

Certification	CCC, CE, FCC , ISO9001
Cooling system	Fanless Cooling
Dimensions	389.2x 324.2 x 57 mm (Subject to the actual)
Enclosure front bezel	Front bezel: Aluminum Back housing: Aluminum
Mounting	Default wall mounting bracket
OS support	Microsoft ® Windows 10, 64bit Default windows 10 English professional version (Activated version)
Weight (Net)	12.1 inch:3 kg 15 inch:4 kg
Package size	12.1 inch:42 x 34 x 14(cm) 15 inch: 51 x 38 x 14 (cm)

LCD Display

Display type	IPS LCD screen
Display size	338.9 (H) x 271.3 (V) mm (Subject to the actual)
Resolution	1280*1024
Luminance cd/m²	500 cd/m²
Viewing angle (H/V°)	178°/178°
Backlight life	50000 hrs
Contrast ratio	1200:1
Aspect ratio	5:4
Lifespan	36 million touches at single point
Touch type	10 Point Capacitive G+G touch screen Single Point Resistance Touch Screen
Response	≤5 ms

System Hardware

CPU	Intel® Core J6412 Processor
Memory	8GB DDR4
Storage	256GB SSD

Environment

Humidity	10~ 95% RH @ 40°C, non-condensing
Ingress Protection	IP65 full protection
Operating Temperature	-10 ~ 50°C
Storage Temperature	-30 ~ 70°C

Accessories

- Power plug&adapter
- Protection interface&cable
- Default wall mounted bracket

Drawing

