

Direct Thermal Label Printer

M4201



Works Perfectly for 4x6 Labels

Durable & Cost Saving

Thermal Label Printer applies newest direct thermal printing technology. No need ink or toner. Up to 152mm/s stable printing speed, about 1 second to print one 4x6" shipping label. Save time and money in your shipping and storage.

Multi-System Compatible

Label Printer can smoothly run on Windows XP, 7, 8, 10, Mac OS. Please choose Bluetooth version and download Soonmark APP to print labels through your smart phones. (Note: NOT compatible with Chrome OS)

Multi-Size Compatible

This printer provides adjustable paper guide rail for small companies, enable them to print various sizes of labels with width range from 20mm-118mm, whether they are bar-code labels or shipping labels.

Easy To Start

Printer comes with a USB disk(the printer driver was loaded in it) and 4x6 fanfold labels to get you an easy start. You can just install the driver and set it up within 5 minutes.








Widely Use

Compatible with most shipping and e-commerce platforms, such as FedEx, USPS, DHL, Amazon, Etsy, eBay, Shopify, etc.




























Professional Technical Support

Provides cost-free after-sales support regarding any printing issues through methods including live chat, phone calls, emails and even remote-desktop operations support if necessary.

Customized Brand Qty

							
	Customized LOGO	Customized Unit box Label	Customized Master Carton Label	Customized Product Label	Customized Carton	Customized Manual	Customized Color
120 PCS	✓	✓	✓	✓	✗	✗	✗
520 PCS	✓	✓	✓	✓	✓	✓	✗
1000 PCS	✓	✓	✓	✓	✓	✓	✓

Tech Specs

 Driver support Windows XP,7, 8,10, Mac OS	 Printing Method Direct Thermal	 Resolution 203 dpi	 Printing Speed 50-152 mm/s	 Printing Width 20-108mm	 Printing Length 25-300mm
 CPU 32-bit RISC CPU	 RAM 8MB	 Flash 4MB	 Media Type Folded paper, roll paper, die-cut label, black mark paper	 Media Width 20-118mm	 Media Thickness 60μm-220μm
 Interfaces Default USB	 Programming Language TSPL	 Control Panel One Feed button (three colors for three different status)	 Power Adapter Input: AC 100-240V, 1A,50-60Hz Output: DC 24V,2.5A,60W	 Dimension (WHD) 232*180*152	 Weight 1.36kg
 Sensors Label edge detection,Out of paper detection, Gap detection,Black mark detection, Coveropen detection	 Operation Environment 41°F(5°C)-104°F(40°C),30%-85%RH				 Storage Environment -4°F(-20°C)-122°F(50°C),10%-90%RH
 Internal fonts 8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.	 QR Code PDF417, Maxicode, DataMatrix, QR code				 Bar code Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13,EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
 Printer & Accessories ①Power adapter ②Power cable ③USB cable ④Label shaft ⑤Manual	 Optional Accessories External Rolls Label Holder				 Safety regulation CCC,FCC,CE

Note: The actual specs of products launched to the market shall take precedence over the info listed in this catalogue; any change may be made without prior notification.

Printer Internal Components



Packing List (default)



Qty per 4 master carton	Unit box size: 335*225*195mm (LWH) Unit box N'W.: 1.8KG Unit box G'W.: 2.31KG	Master carton size: 486*358* 430mm (LWH) Master Carton N'W.: 7.2KG Master Carton G'W.: 10.29KG
--------------------------------	---	--

Note: The actual specs of products launched to the market shall take precedence over the info listed in this catalogue; any change may be made without prior notification.