



Front Scanner Module



Rear Scanner Module



Desktop Design



Wi-Fi Supported



Capacitive Touch



Light Weight



Built-in Speaker

Specification:

System	Android 7.1		Communications:	WIFI:	IEEE 802.11b/g/n	
CPU	RK3368,Octa core,1.5GHz;			Bluetooth:	BT2.1+EDR/3.0/4.0/4.1/4.2 BLE	
GPU	PowerVR G6110			Ethernet:	10/100M adaptive	
RAM/ Storage	2G/ 8G		Weight	Net Weight:	1.2kg	
Display	Size:	10.1inch		Gross Weight:	1.9kg	
	Resolution:	1280*800	Ports	1* SIM Card slot(optional) 1* RJ12 6P6C cash drawer		
	Type:	Capacitive		1* TF Card slot 1* RJ11 6P4C com		
Speaker	Built-in 2W speaker			1* 3.5mm Jack 4* USB 2.0 TypeA		
Dimension	251*157*270	(L*W*H)		1* Power port 1* RJ45 LAN		
Environment	Working temperature: -10℃-40℃		Storage Temperature: -20℃-55℃		Humidity: 20%-90% RH	

Rear Scanner Module

Prompt mode:	Buzzer, LED indicator
Trigger mode:	Command trigger, automatic induction trigger, continuous trigger
Setting method:	Scan code setting, command setting
Interface:	USB HID keyboard
Recognition angle:	Rotation 360°, left and right tilt ±45°, front and back tilt ±45°, recognition accuracy ≥5mil
Reading code:	1D: Code128、Code39、EAN、UPC、Code93、ISBN-13、Interleaved 2 of 5
	2D: QR Code

Front Scanner Module

Prompt mode:	Buzzer, LED indicator
Trigger mode:	Command trigger, automatic induction trigger, continuous trigger
Setting method:	Scan code setting, command setting
Interface:	USB HID keyboard
Recognition angle:	Rotation 360°, left and right tilt ±45°, front and back tilt ±45°, recognition accuracy ≥5mil
Reading code:	1D: Code 128、EAN-13 、EAN-8、UPC-E、UPC-A、ISBN、ISSN、Code11、ITF-25 (Interleaved 2 of 5) 、Code39、Code93、Code32、Codabar、Matrix 2 of 5、Industrial 25、IATA 25、MSI Plessey
	2D: QR Code、Micro QR、Data Matrix 、PDF417