



Features:

- 260mm/s printing with low noise
- Over-temperature protection
- Supports 1D & 2D barcode printing
- Supports automatic paper cutting
- Supports Linux system drivers
- Supports for OPOS drivers
- Supports wall mounting
- Supports cash drawer

Specification

Printing method	Direct thermal
Printing density	576 dots/line or 512 dots/line
Printing speed	Max. 260mm/s
Print width	72mm
Paper width	79.5±0.5mm
Paper roll diameter	60mm
Auto cutter	Partial cut
Interface	COM+USB+LAN
Character set	ANK character set, Simplified Chinese character set (GB2312)
Character size	ANK character: Font A:1.5x3.0mm (12x24) Font B:1.1x2.1mm (9x17) Simplified/Traditional Chinese:3.0x3.0m (24x24)
Barcodes supported	1D barcode: UPC-A/UPCE/JAN13(EAN13)/JAN8(EAN8)/CODE39 /ITF/CODABAR/CODE93/CODE128 2D barcode: QRCode / PDF417
Power adapter	DC24V/2.5A
Working life	Printer head: 150km Auto cutter: 1.5 million times
Working environment	0~45°C; 10~80% RH
Storage environment	-10~60°C; 10~90% RH
Dimension / Weight	190.16x140x134.64 mm (L*W*H) / 1.0 kg

