

AIO INDUSTRIEL INTERACTIVE WITH STAND

Model SK-43GB-2



Delivering Genuine Benefits

- All you need - the SK-43GB collaborative board ships with integrated touch and speakers
- Intel® Core® i3 3rd generation Dual-core Processor with 4GB DDR3 SDRAM, 128GB.
- Robust and reliable touch experience - utilizes integrated 10-point touch that can be used with the included pens or fingers.
- Software to meet your needs - the SK-43GB comes preloaded with interactive whiteboarding.
- Future-proof PC option & reduced footprint – the integrated Slot-In PC using the integrated OPS option slot future-proof your investment while reducing the product footprint and installation efforts.
- Includes additional inputs that support HDMI, USB connectivity so that touch can be supported by simply switching inputs.

senke®

File Browsing

• You can browse files saved in the system and on connected external USB devices, such as documents, whiteboard writings, videos, pictures, and audio.

Displayable / playable files

	Supported file systems
Still Image	JPG, JPEG, JPE, PNG, BMP, GIF
Motion Image	FLV, 3GP, AVI, M4V, MKV, MOV MP4, MPG, MPEG, TS
BGM	AAC, FLAC, M4A, MP2, MP3, OGG, WAV

Introduction

Good communication is key in the office or classroom. The SK-43GB Series puts the tools you need to achieve it at your fingertips. Start presenting instantly on the whiteboard, import and modify media wirelessly, brainstorm ideas with teams in remote locations, and email progress direct from the display. Do it all from an intuitive touchscreen with fewer cables and no need for a remote. The SK-43GB series doesn't just save time and money, it's a complete end-to-end solution engineered for success at the highest level.

Specifications

LCD MODULE

Viewable image size (diagonal)	43 inch
Active screen area (W × H) (mm)	530 × 943
Display type	TFT LCD screen
Native resolution	1920 × 1080
Brightness (typical with AG glass)	350 cd/m ²
Contrast ratio (typical)	3000 : 1
Aspect Ratio	16 : 9
Viewing angle [°]	178 horizontal / 178 vertical (at CR>10)
Colour	10bit, 1.07B
Response time (typical)	≤5ms
Backlight	Direct LED backlight
Backlight Life	50000 hours

INTEGRATED TOUCH PANEL

Method	Infrared touch
Multi-touch	10 point touch screen
Operating system	Windows 10 (Default windows 10 English professional trial version) Android (optional)
Processor	Intel® Core® i3 3rd generation dual-core Processor
Memory	4GB DDR3 SDRAM
Storage	128GB

POWER

Power requirement	100-240 V
-------------------	-----------

ENVIRONMENTAL CONDITIONS

Operating temperature	0°C to 40°C
Operating humidity	10% to 90%
Operating hours	12 / 7

CONNECTIVITY

Power x 1
Audio input x 1
Audio output x 1
HDMI x 1 USB x 4
VGA x 1
LAN x 1 (RJ-45)
USB x 6

Interface

PROTECTIVE GLASS

Material	3.0 mm Tempered glass
Surface treatment	Anti-glare coating (55" and above size can make)
Surface hardness	6-7 H

PHYSICAL SPECIFICATIONS

Dimensions (with wall mount : W × H × D) (mm)	577 × 988 × 61.1
Packaging dimensions (W × H × D) (mm)	689 × 1064 × 121
Net weight (with wall mount)	13.3 kg
Gross weight (with box)	16.6 kg
Mounting interface	300 × 300
Supported orientation	Landscape

wall mount bracket

Drawing

Unit (mm)

