

Industrial Touch Panel PC

Model SK-21.5GB-2



Features

- 21.5" IPS LCD with 50K Lifetime LED Backlight
- RK3288 2GB 16GB Android 10
- Supports wide operating temperatures -10~50°C
- IP65 certified front panel protection
- 10 Point Capacitive G+G Touch Screen

Introduction

The SK-21.5GB-2 touch all in one pc with a 21.5" IPS LCD screen, low power embedded RK3288 2GB 16GB Android 10 provides computing performance in a compact system. To enhance its durability, the SK-21.5GB-2 is designed with IP65 front protection, aluminum front bezel and 10 point Capacitive G+G touch screen. It supports wide operating temperatures -10~50°C and includes full size mini-PCIe slot to extend the functionality and meet a variety of automation applications needs.

Specifications

General

Certification	CCC,CE, FCC ,ISO9001,BIS,CCC
Cooling system	Fan
Dimensions	52.7*32.2*112CM
Enclosure front bezel	Front bezel : Aluminum Back housing : Cold rolled steel plate
Mounting	Default wall mounting bracket
OS support	Android 10
Optional color	Silver or black
Weight (Net)	7 kg
Weight (Gross)	12kg
Package size	60*15*44CM

System Hardware

CPU	RK3288
Memory	2GB
Storage	16GB
	Power x1
	HDMI x1
	LAN x1 (RJ-45)
	USB x2
	Audio input x1
	Audio output x1

I/O

LCD Display


Display type	IPS LCD screen
Display size	477 ×268.5 mm (H×V)
Resolution	1920 × 1080
Max. colors	16.7 M
Luminance cd/m²	250
Viewing angle (H/V°)	178°/178°
Backlight life	50000 hrs
Contrast ratio	1500:1
Aspect ratio	16:9
Lifespan	36 million touches at single point
Touch type	10 Point Capacitive G+G touch screen
Response	≤5 ms

Environment

Humidity	10~ 95% RH @ 40°C, non-condensing
Ingress Protection	Front panel: IP65
Operating Temperature	-10 ~ 50°C
Storage Temperature	-30 ~ 70°C

Accessories

- Adaptor (DC 12-19V) (cable 1 meter)
- Power plug (cable 1.2 meter)
- K type bracket



REMOTE OPERATION

