

# Full Page Passport Reader

Full Page Passport Reader is a compact, fast and multi-functional document reader based on OCR technology. It is designed for extracting data from ICAO standard travel documents. It provides ideal solutions for identifying Passports, Visa, ID cards, Driver License and other travel documents.



QR1000(I)

#### **Features**



Read ICAO compliant & Non-ICAO documents



Combine with high accuracy OCR SDK



Obtain digital data from contactless chips (Opt)



Applicable for self-service kiosk



Capture images in white, IR Illuminations



Provide OCR customization service

### **Applications**



Airport **Border Control** 



Security Access Control



Hotel **Property Management** 



Finance Payment Process

# **Specification**

#### **Supported Documents**

ICAO 9303 standard compliant documents:

ID-1 (Identity Card)

Machine Readable Zone ID-2 (Visa)

ID-3 (Passport)

Visual Inspection Zone Customization based on clients' requirements

> 1D: Code 128, Code 39, Interleaved 2 of 5 Barcode 2D: PDF 417, QR Code, Data Matrix, Aztec Code

ma	ae	
	-	

		image
F	Resolution	500 DPI
III	umination	Visible, IR (850nm)
Co	olor Depth	24 bits/pixels
	Sensor	CMOS, 5.0 Megapixels (2592*1944) JPG, BMP,
Imag	ge Format	PNG
Fie	ld of View	127mm*88mm
		Software
		Windows 7,8,10, Vista, XP (32/64 bit WHQL certified

ed) Supported Operation

Windows Server 2003 & 2008 (32/64 bit) System

Linux Ubuntu, CentOS, RedHat

Android


Complete OCR SDK including DLLs, Development kit


OCXs, WebSocket, Samples and Demo program


**Programming Languages** C#, C/C++, Java, Delphi, Visual Basic 6.0, VB.NET

> Security Check UV Dull Paper Check; MRZ Comparison;

Portrait Comparison; IR B900 Ink check.







Hardware		
Dimension	175*199*140mm(width*depth*height)	
\\\\-\!\-\!\-\!\-\!\-\!\-\!\-\!\-\!\-\!	1.75kg (Net)	
Weight	2.00kg (Gross)	
Interface	USB 2.0	
Status LEDs	Power, Ready, Error and Warning	
Buzzer	Build-in buzzer	
Power	Input: AC 100~240V, 50-60Hz, 0.8A	
Power	Output: DC 12V, 2A	
Operating humidity	20%-95%(non-condensing)	
	-10°C to 50°C operating	
Operating temperature	-20°C to 50°C storage	
Warranty	1 year warranty, extensible	

# Sinosecu Technology Corporation

- **(** +86(0)1082525969
- info@sinosecu.com.cn