

PRODUCT FEATURES



- Aluminum housing and fanless design.
- Customized main board with few cable connections makes neat frame.
- Plug and play HDD/SSD.
- Rotatable and inseparable cable cover.
- VFD display and secondary monitor are available.
- Peripheral connection cables could easily go through the base.
- Plug-in Dallas Lock / MSR modules without cable connection.



Excellent Heat Sinking



External USB Port



Multi-ports Available



Pluggable 2.5" HDD/SSD

SPECIFICATIONS

CPU	Intel Baytrail-D,Celeron J1900,2.0GHz up to 2.41GHz , TDP 10W	Extended Slots	1 x MINI-PCIE (for 4G/WIFI), 1 x Micro-SIM (on board)
Graphics	Intel HD Graphics	Customer Display	VFD or 9.7" secondary monitor (option)
Graphic Output	VGA, LVDS,EDP	I/O Ports	1 x DC24V_IN, 1 x DC12V_OUT
Display	15" TFT LCD, 1024 x768(max.)		1 x RJ11 for cash box
Viewing Angle	45 degree adjustable		3 x RJ48 for RS232
Touch Solution	15" Capacitive touch panel		4 x USB2.0 + 1 x USB2.0
RAM	DDR3L 1333/1600MHZ, 4GB as standard, optional up to 8GB		1 x RJ45 for LAN
Storage	64GB SSD as standard, optional up to 256GB, 1 x SATA, 1 x M-SATA	O.S. Compliant	1 x VGA
Audio	Realtek ALC 662HD (on board)	Input Power	1 x LINE-OUT
LAN	Realtek RTL8106E-CG (on board)	Power Supply	DC24V
		Power Supply	100 ~ 240V / 47 ~ 63Hz
		Work Environment	-10 ~ 60 degrees, 0% ~ 95%

